

Smart Wireless Sensors in an Open System Architecture

Defense Science & Technology Seminar on Emerging Technologies
Condition-Based Maintenance /
Predictive Diagnostics
17 July 2000

Richard W. Lally President

Industry/Academia/Government oceana sensor Partnership





Wireless Smart Sensors **Open System Architecture** for CBM/PHM











Why OSA CBM?



- Ease of Component Integration for Solution Offering
- Faster Market Development
- Lower Cost

= Greater Profitability.



Key OSA Technologies



Internet Connectivity HTTP/TCP/IP

Standard Language CBM XML

• BluetoothTM Wireless Technology

Standard Transducer Object Model IEEE 1451

AAAV CBM (ONR TOC FNC Funded)



Application Platform

Platform Health Monitoring



Operational Commander


In-stride Logistics

Technical Support

Platform Information Network

SHMTM

System Health Monitor



- CPU & Controllers
- Information Network Interface
- Information Archive, prognostics

ICHM™ Intelligent Component Health Monitors



ICHMTM 1 **Intelligent Bearing Health Monitor**




ICHMTM 2 **Intelligent PTM** Health Monitor











Communications

Diagnostic Processor

General Purpose Processing

Signal Processing

Signal Conditioning

Power Interface/Generation

Sensing Elements


Self-calibration/Active Cancellation

Intelligent Component Health Monitor



Wireless ICHMTM Architecture







IEEE 1451



.1 Defines Standard Transducer Object Model

- .2 Defines the interface for integration of digital sensors to microprocessors
 - Physical interface
 - Transducer Electronic Data Sheet (TEDS)
 - Protocol



ICHMTM - ASIC



- Signal Conditioning
 - Low noise preamplifier buffer, filters
- Analog-to-Digital Converter
 - Delta-sigma architecture
 - Single supply (3-5 V)
 - Adaptive response: tradeoff resolution vs. bandwidth vs. power consumption
- Self-Test



ICHMTM MCU & Bluetooth Radio




- •Micro-Controller Unit (MCU)

 DSP Algorithms, IEEE 1451, Radio Host Controller Interface (HCI)
- •Memory
 Program, Data, TEDS, Calibration
- •RF communications
 - Low Cost (\$5) Low power, ISM band
 - Multiple access 1 Mbit/sec Bandwidth
 - Secure Send & receive









In 2001 ~ 1 in. Cube

Military/Commercial



























